

Technical Data Sheet for the Anti-scratch Poly-cotton Canvas

Features

- Matt surface and Yellow Back
- 80% Polyester + 20% Cotton
- Eco solvent/UV/Latex
- Anti-scratch

Applications

- Indoor and outdoor signage/decoration
- Block mounts
- Canvas printing
- and more...

Material Details

| PROPERTIES | TEST METHOD | METRIC | IMPERIAL |
|------------------|-----------------|---|----------------|
| Standard width | - | 0.61/0.914/1.07/ 1.27/ 1.37/ 1.52/1.82m/3.1m | - |
| Standard Length | - | 18m / 30m | - |
| Thickness | - | - | - |
| Weight | - | 370g/sq.m+/-20gsm | - |
| Base Fabric | DIN 60001 | 80% Polyester + 20% | - |
| Tensile strength | DIN EN ISO 1421 | 848 x 354N/5cm | 94x39 lbs/Inch |
| Tear strength | DIN 53363 | 31 x 18N | 7 x 4lbs |

Ink printability

- Solvent
- Eco solvent
- UV
- Latex
- Screen printing
- Dye sublimation transfer
- Dye Sublimation Direct
- Water based

PLEASE NOTE: All of the above information is only a guide; please test the Poly-cotton Canvas compatibility before final use of a project.

Call one of our friendly sales reps on 087 056 3231 or visit our Durban or Jo'burg offices today for more information.