# Technical Data Sheet for ProMedia 5 year self adhesive vinyl

## Features

- Gray Removable glue
- Indoor & outdoor signage and wide-format digital printing such as vehicle advertising,outdoor durable signage and product labels
- Matte or gloss finish
- With Single-side PE coating liner, Wood Pulp Bubble Free Liner Paper

| PROPERTIES | | METRIC | IMPERIAL |
|---|---|---|---|
| PVC Film | Composition | Finished, white Polymeric PVC film | |
| | Thickness (+/-10%) | 0.08mm | 80micron |
| | Weight (+/-10%) | 110g/m² | 3.2oz/sq.yd. |
| | Shrinking | <0.7% | |
| Adhesive | Opaque | 80% | |
| | Adhesive Type | Acrylic adhesive, removable glue | |
| | Temperature Range | -20~70°C | |
| | Tack (N/m) | 500 (test while adhering to stainless steel) | |
| Release paper weight | Final Tack (N/m) | 500 (test while adhering to stainless steel) | |
| | Type | Kraft paper with one-side silicone backing | |
| | Color | White | |
| | Weight (+/-5%) | 140 | |
| Storage Period | | 1 year (Storage temperature of 22°C relative humidity of 50~55%) | |
| Durability | | 5 years based on Central European weather conditions. Actual durability may vary under South African climate conditions. | |
| Width | | 0.914/ 1.07/ 1.27/ 1.37/ 1.52m | 36"/ 42"/ 50" /54" /60" |

## Ink Printability

- Solvent
- Eco-solvent
- UV
- Screen printing

**PLEASE NOTE:** This data sheet serves as just a guide. It is recommended that you please test this product before final use pn a project.