Technical Data Sheet for ProMedia bubble-free monomeric

Features

- Grey Removable glue
- Indoor & outdoor signage and wide-format digital printing such as vehicle advertising, outdoor durable signage and product labels
- Matte or gloss finish
- Release Paper with Single-Side PE Coating, Wood Pulp Bubble Free liner paper

PROPERTIES		METRIC	IMPERIAL
PVC Film	Composition	Finished, white Monomerica PVC film	
	Thickness (+/-10%)	0.10mm	/
	Weight (+/-10%)	120g/m²	/
	Shrinking	<0.9%	
Adhesive	Opaque	80%	
	Adhesive Type	Acrylic adhesive, removable glue	
	Temperature Range	-20~70°C	
	Tack (N/m)	450 (test while adheing to stainless steel)	
Release paper weight	Final Tack (N/m)	450 (test while adheing to stainless steel)	
	Type	Kraft paper with one-side silicone backing	
	Color	White (pure wood pulp paper)	
	Weight (+/-5%)	145	
Storage Period		1 year (Storage temperature of 22°C relative humidity of 50~55%)	
Durability		2-3 year (Used under proper condition, eg. No industrial)	
Width		0.914/ 1.06/ 1.27/ 1.37/1.52m	36"/ 42"/ 50" /54" /60"

Ink Printability

- Solvent
- Eco-solvent
- UV
- Screen printing

PLEASE NOTE: Durability is based on central european weather conditions. This data sheet serves as just a guide. It is recommended that you please test this product before final use on a project.